

PRODUCT

ANALOG CAMERA

Standard Camera

HSB4220 W



- 1/3" PIXIM 410K CMOS
- 520TV Lines
- Superior Wide Dynamic Image Quality & Digital Pixel System
- Built-in OSD Function
- Available ATW, AGC, DSS etc
- C / CS Mount Lens available

Specification

Signal System	NTSC	PAL
Pick-up Device	1/3" PIXIM CMOS (Dramatically Dynamic range sensor)	
Total of Pixel	742(H) X 552(V)	
Horizontal Resolution	520Horizontal TV Lines (color)	
Scanning System	525 lines interlaced	625 lines interlaced
Synchronization	Internal / External	
Video Output	1.0Vp-p / 75ohm Composite	
Iris Control	DC Lens, Video Lens, Manual Lens	
Sensitivity	0.08Lux (DSS on) with F1.2 Lens	
S/N Ratio	48dB or more	
Dynamic range	120dB(max), 95dB(typical)	
Shutter Speed	1/60 - 1/100,000	1/50 - 1/100,000
Lens Mount	C/CS mount	
AGC Control	0 - 36dB	
OSD Menu	Built - in	
Supplied Voltage	DC 12V (10V - 18V)	
Power Consumption	Max 2.0W	
Operating Temperature	-10℃ ~ 55℃	
Storage Temperature	-20℃ ~ 70℃	
Operating Humidity	under 90% Non-condensing	
Storage Humidity	under 95% Non-condensing	