

Bullet Camera



HSB6220VTD-32

- 1/3" SONY Super HAD COLOR CCD
- 540 TV Lines
- Built-in Filterchangeable Vari Focal Lens (ICR)
- Built-in 32pcs Giant IR-LEDs
- Multi OSD Function built-in
- Built-in Cable Bracket
- Option - Dual Power (DC12V/24VAC)

Specification

Signal System	NTSC	PAL
Image Sensor	1/3 inch SONY Super HAD CCD	
Scanning System	2:1 Interlace	
Scanning Frequency(H)	15.734kHz	15.625kHz
Scanning Frequency(V)	59.94Hz	50Hz
Video Output	VBS 1.0 Vp-p (75 ohm Load)	
Sync. System	INT	
Effective Pixels Number	768(H) x 494(V), 380K pixels	752(H) x 582(V), 440K pixels
Horizontal Resolution	540 TV lines	
S/N Ratio	More than 52dB (AGC OFF)	
Min. Illumination	0.1 Lux(Color) / 0.03 Lux(B/W) / 0.0001 (Sens-up) at F1.2, 0Lux at IR-LED ON	
Lens	6.0 ~ 50.0 mm Filter changeable(ICR) DC Auto Iris Varifocal	
O.S.D	Built-in	
Supplied Voltage	DC12V ± 10%	
Operating Temp.	-10°C to +55°C	
Storage Temp.	-20°C to +70°C	
Dimension	90Φ Housing	