

# ANALOG CAMERA

## Dome Camera



### HSB7220FTD

- High Sensitive 1/3" SONY Super HAD Color CCD
- 540 TVL Resolution
- True Day & Night (ICR)
- Built-in Fixed 3.6mm Board Lens
- Low Sensitivity of 0.05 Lux
- OSD Menu & VBS-EXTRA for connection to LCD monitor (Option)
- 100mm Dome Size

### Specification

ITEM	NTSC	PAL
Image Sensor	1/3" SONY Super HAD Color CCD	
Scanning System	2:1 Interlace	
Scanning Frequency(H)	15.734 KHz	15.625kHz
Scanning Frequency(V)	59.94 Hz	50Hz
Sync. System	Internal	
Effective Pixels Number	768(H) x 494(V) 380K	752(H) x 582(V) 440K
Horizontal Resolution	540 TV Lines	
Video Output Level	1.0 Vp-p (75 Ohms, Composite)	
S/N Ratio	50dB (AGC Off)	
Lens	Built-in Fixed Lens (3.6mm)	
Iris Control	Fixed	
Min. Illumination	0.5 Lux/F1.2 (Color), 0.05 Lux/F1.2(B/W)	
Back Light Control	Auto	
White Balance	Auto	
Electronic Shutter Speed	Auto (1/60~1/10,000)	Auto (1/50~1/10,000)
Supplied Voltage	DC 9V ~ 15V (Recommendation DC12±0.5V)	
Power Consumption	Max. 160mA / 1.8W	
Dimensions	100(Ø)	
Weight (Net)	Approx. 280g	